

Uniclass L331	EPIC C311
Cl/SfB	
Yq4	

November 2008

# Flowable Grout

## Product Datasheet

## EuroMix Flowable Grout

### 1. Identification

#### 1.1 Introduction

EuroMix Flowable Grout is a high performance structural grout ideal for grouting of precast concrete panels, designed to be used in grout pumps or where placement is restricted.

It is delivered in silos, prepacked 25kg bags or 1 tonne sacks.

#### 1.2 Authority

The individual components of this product comply with the requirements of BS/IS EN 206-1: 2002 and is manufactured under a BSI/NSAI registered ISO 9001 Quality System.

Materials used comply with the following standards:

Sand	BS EN 13139: 2002
Cement	BS EN 197-1: 2000 (UK) IS EN 197-1: 2000 (Ireland)
Aggregate	BS EN 12620: 2002

Admixtures do not contain calcium chlorides. Water added on site should be clean and free from impurities.

#### 1.3 General Advantages

- Fine aggregate
- Consistent mix proportions
- Pump application
- Guaranteed strengths
- Min wastage, maximum output

### 2. Description

#### 2.1 Manufacture

Raw materials and end products are subject to regular quality control procedures and testing.

Dried sand and other materials are weighed and mixed under computer control with rigorous quality assurance procedures.

#### 2.2 Compressive strength classes

EuroMix Flowable Grout can be supplied in strength classes to suit the requirements of the specifier complying with BS EN 206-1 as set out in the table below:

##### Characteristic Strength N/mm<sup>2</sup>

1 day	10 N/mm <sup>2</sup>
7 days	50 N/mm <sup>2</sup>
28 days	70 N/mm <sup>2</sup>

Based on water demand of 3.75 litres per 25k bag and density 2200 kg/m<sup>3</sup>

Strength Class	C24/30	C28/35	C32/40
Cylinder	24	28	32
Cube	30	35	40

#### 2.3 Colours

Natural grey.

### 3. Performance

CPI EuroMix Flowable Grout is specially designed to give excellent workability when wet, and to harden to a durable finish.

#### 4. Sitework

The enhanced flexibility of the dry mortar system offers several options on site:

- Direct discharge into a skip or mobile pump
- Transfer of dry material to a remote mixing station

When a silo is used, it should be placed on a firm level base measuring at least 3m x 3m. It is delivered complete with all necessary mixing equipment, which can be used by any site operative once a EuroMix Service Technician has given them basic training.

After connecting power and water supplies, the system is ready for use. Once the water flow rate is adjusted to give concrete of the required workability, it is simply a question of push-button operation to produce consistently high quality concrete whenever it is needed.



**EuroMix**

## 5. Prices and Conditions of Sale

Our Sales Office will be pleased to provide quotations for specific projects. All quotations are subject to our Conditions of Sale – a copy of which is available on request.

## 6. Supply

EuroMix Flowable Grout is available throughout the market area of each plant.

Silos are delivered with up to 16 tonnes of dry mortar and may be refilled by bulk tanker.

EuroMix Flowable Grout may also be delivered in minisilos or pre-packed 25kg bags.

## 7. Health & Safety

For health and safety information see Material Safety Datasheet.

## 8. Technical Services

Fully trained Service Technicians are available at all times to provide on-site support to users of the EuroMix Dry Mortar System. Our Technical Advisory Service is available to give expert advice on the specification or use of EuroMix Flowable Grout.

---

### Dublin

Laraghcon,  
Lucan,  
Co. Dublin  
Tel: +353 (1) 630 2700  
Fax: +353 (1) 628 0331



Helpline: **01 630 2700** (Ireland)  
Visit us at: **[www.euromix.com](http://www.euromix.com)**  
E-mail: **[info@cpieuromix.com](mailto:info@cpieuromix.com)**

